

FRO600



FRO600

TrustLink

- GA
- 33mm
- 100
- 1s
- 99.99%
- 32
- SDK
- TrustLink

- OA
-
-
-
-

FRO600

		110*110*45mm(L*W*H)
		460g
		/ /
		40.64*38.10mm
		40.64*38.10mm
		800*750pixel
		500dpi
		150
		2%
		USB 1.0/2.0
		5.0V ± 5%
		200mA
		-10 55
		20% 90 R.H
	PIV-071006 IQS for Single Finger Reader FIPS 201 for PIV of Federal Employees and Contractors IAFIS-IC-0110(V3.1) CJIS-WSQ compression specification WSQ 10~20 NISTIR7151 ISO/IEC19794-2 ISO/IEC19794-4 ISO/IEC19794-5 ISO/IEC 15444-1:2004 JPEG 2000 image coding system ANSI/NIST-ITL-1-2007 ANSI/NIST-ITL-2-2008	
	Windows XP/2003(32bit/64bit), Windows Vista/2008(32bit/64bit), Windows 7/8(32bit/64bit)	



+86 400-6030-161
 +86 755-26719930
 : Marketing@aratek.com.cn

T2-A A



©深圳市亚略特生物识别科技有限公司。规格如有变更，恕不另行通知。
 确认在本文件中使用的所有商标及所载的任何材料，禁止未经授权的使用。